



## PRODUCT DESCRIPTION

Dimensions	2038mm x 190mm
Thickness	12mm
Bevels	4
Loc System	5G Loc under licence of Välinge Innovation AB
Classification of use	Class 23/33 According to European Standard EN13329

	Contains	m <sup>2</sup>	ft <sup>2</sup>	Weight
1 pack	4 planks	1,55 m <sup>2</sup>	16,67 ft <sup>2</sup>	17 kg
1 pallet	72 packs	111,52 m <sup>2</sup>	1200,38 ft <sup>2</sup>	1248 kg

## COMPOSITION

Surface layer	Direct laminated paper, impregnated with melamine resin
Substrate	Moisture resistant High Density Fiberboard (HDF) treated with HydroPlus water repelling technology
Backing	Direct laminated paper, impregnated with melamine resin

## TESTED VALUE

Abrasion resistance	EN13329	AC5 (IP≥6000)
Impact resistance	EN13329	Small ball : ≥ 15 N - Big ball : ≥ 1000 mm
Thickness swelling	EN13329	12% (requirement ≤ 15%)
Fire resistance	EN14041	Cfl-S1
Formaldehyde	EN14041	E1
Slipperiness	EN14041	DS
Density	EN323	900 kg
Resistance to staining	EN438	5 (groups 1+2); 4 (group 3)
Resistance to cigarette burns	EN438	4
Effect of a furniture leg	EN424	No damage (foot type 0)
Effect of a castor chair	EN425	No change in appearance or damage
Thermal resistance in combination with underlay Excellence Plus		0,12 m <sup>2</sup> K/W – Suitable for floor heating/cooling. Detailed instructions on <a href="http://www.berryalloc.com">www.berryalloc.com</a>

## METHOD

## TEST RESULTS

## CERTIFICATES/LABELS

- Sustainability of forests: PEFC certified (07-31-229)
- Labelling according to French VOC emission regulation: A+
- CARB: Phase II compliant
- DOP: 170-DL3313-1

## WARRANTY

- Lifetime Residential Warranty
- 6 Years of Commercial Warranty
- Warranty conditions on [www.berryalloc.com](http://www.berryalloc.com)

