



## PRODUCT DESCRIPTION

Dimensions	1288mm x 155mm
Thickness	8mm
Bevels	4
Loc System	5G Loc under licence of Välinge Innovation AB
Classification of use	Class 23/32 According to European Standard EN13329

	Contains	m <sup>2</sup>	ft <sup>2</sup>	Weight
1 pack	9 planks	1,80 m <sup>2</sup>	19,34 ft <sup>2</sup>	12,9 kg
1 pallet	70 packs	125,77 m <sup>2</sup>	1353,81 ft <sup>2</sup>	916 kg

## COMPOSITION

Surface layer	Direct laminated paper, impregnated with melamine resin
Substrate	Moisture resistant High Density Fiberboard (HDF)
Backing	Direct laminated paper, impregnated with melamine resin

## TESTED VALUE

Abrasion resistance
Impact resistance
Thickness swelling
Fire resistance
Formaldehyde
Slipperiness
Density
Resistance to staining
Resistance to cigarette burns
Effect of a furniture leg
Effect of a castor chair
Thermal resistance in combination with underlay Excellence Plus

## METHOD

EN13329
EN13329
EN13329
EN14041
EN14041
EN14041
EN323
EN438
EN438
EN424
EN425

## TEST RESULTS

AC4 (IP≥4000)
Small ball : ≥ 12 N - Big ball : ≥ 750 mm
12% (requirement ≤ 18%)
Cfl-S1
E1
DS
900 kg
5 (groups 1+2); 4 (group 3)
4
No damage (foot type 0)
No change in appearance or damage
0,08 m <sup>2</sup> K/W – Suitable for floor heating/cooling. Detailed instructions on <a href="http://www.berryalloc.com">www.berryalloc.com</a>

## CERTIFICATES/LABELS

- Sustainability of forests: PEFC certified (07-31-229)
- Labelling according to French VOC emission regulation: A+
- DOP : 170-DL3213-1

## WARRANTY

Lifetime Residential Warranty  
5 Years of Commercial Warranty  
Warranty conditions on [www.berryalloc.com](http://www.berryalloc.com)

